



## Oil Based Gloss Product Advice Sheet

### Description

A traditional, alkyd-based paint for use on interior or exterior surfaces. Flows to a smooth, hard wearing, high gloss finish resistant to repeated washing and condensation. Ideal for use in kitchens and bathrooms. Conforms to BS 7664.

### Surfaces

Suitably primed woodwork, primed steel and non-ferrous metals, pretreated galvanised metal. Can also be used on suitably prepared plaster and cementitious surfaces.

**Pack Sizes** 2.5 litres, 1 litre

**Colour Range** Little Greene and others on request.

**Spreading Rate** Up to 16 square metres per litre depending on surface profile.

**Drying Rate** Normally touch dry in 3-5 hours. Recoatable after overnight drying.

**Environment** Manufactured to BS EN ISO 14001:2004 standards  
VOC content High (29%)  
Complies with European Commission VOC Directive 2004/42/CE

### Technical Information

Sheen Level 85%

Spraying (Conventional) Dilute 5% with white spirit  
(Airless) Use 13 – 15 thou tip

Specific Gravity 0.90-1.08 depending on colour

Solids by Volume 51% approximately

Dry film Thickness 30-35 microns per coat on smooth surfaces



# Oil Based Gloss Product Advice Sheet

## Preparation

Surfaces must be clean, dry and free from loose and flaking material, dirt, grease etc. Repairs should be carried out prior to painting. Areas contaminated with fungal or algal growth should be treated with a proprietary fungicidal wash or with 25% household bleach before painting. Surfaces previously treated with gloss paint should be lightly abraded before painting. Highly alkaline surfaces should be primed with an alkali-resisting primer. For maximum protection a coat of Universal Primer Undercoat is recommended after priming.

## Application

Stir well before use. May be applied without thinning by brush, roller or airless spray. Up to 2% thinning with White Spirit should be carried out to ease application under cold conditions. Apply 1 or 2 coats as required.

## Clean up

Equipment should be cleaned with white spirit immediately after use.

## Precautions

Always read the can label before use. Ensure maximum ventilation during application and drying. Do not apply below 5°C. Drying will be slower below 10°C.

## Disclaimer

All the information submitted on this sheet is correct to the best of our knowledge and experience. The Little Greene Paint Company reserves the right to modify data and systems sheets and procedures with reference to usage and application without further notice. The information supplied does not absolve users from responsibility to carry out their own tests and experiments, nor does it imply any legally binding assurance of certain properties or suitability for any specific purposes. Conditions of application and service may be beyond our control, so no liability whatsoever can be accepted on the basis of the information supplied herein.